



- 1 Aesthetically appealing look with clear contour lines. Available in variety of colours: woodgrain and acrylicolor range. Please visit GEALAN's website [www.acrycolor.net](http://www.acrycolor.net) for more information
- 2 Five or six chamber extrusion design with installation depth of 74mm offers superior sound and thermal insulation value of  $U_f = 1.3 \text{ W/m}^2\text{K}$  ( $R_f = 0.76$ )
- 3 Large main chamber for steel reinforcement provides great stability even in extreme wind zones
- 4 EPDM compression double rubber seals ensure superior weathertightness and airtightness
- 5 16mm Eurogroove rebate accommodates multipoint locking hardware for great security and weather/air tightness
- 6 Deep rebates allowing glazing units from standard 24mm double glazing up to 48mm triple glazing
- 7 All EuroWindows and doors are glazed from the inside with clip on glazing beads. This has many advantages, such as easy glass exchange if need arises, great security as they can not be removed from outside, easy installation procedure in high-rise or difficult access situations.
- 8 Easy to clean smooth rebate
- 9 The fins allow easy attachment of various GEALAN auxiliary profiles for customized installation situations
- 10 Optional patented ventilation system GECCO provides a controlled exchange between inside and outside air and improves the air quality inside the

