



- 1 Aesthetically appealing look and timeless appearance with clear contour lines. Available in variety of woodgrain finishes and highly durable "acrycolor" range. Please visit GEALAN's website www.acrycolor.net for more information.
- 2 Six chamber extrusion design with installation depth of 82.5mm offers superior sound and thermal insulation value of $U_i = 0,89 \text{ W/m}^2\text{K}$ ($R_i = 1.12$)
- 3 Foam core insulation to achieve Passive House standard
- 4 EPDM compression double rubber seals ensure superior weather tightness and airtightness
- 5 The center seal level in the window frame further enhances the thermal insulation, air and weather tightness.
- 6 Large main chamber for steel reinforcement provides great stability even in extreme wind zones
- 7 16mm Eurogroove rebate accommodates multipoint locking hardware for great security and weather/air tightness
- 8 Deep rebates allowing usage of high performance triple glazing of up to 52mm thick with $U_g = 0.5$ ($R_g = 2$)
- 9 All EuroWindows and doors are glazed from the inside with clip on glazing beads. This has many advantages, such as easy glass exchange if need arises, great security as they can not be removed from outside, easy installation procedure in high-rise or difficult access situations.
- 10 26mm deep glass edge cover design further enhances the thermal insulation around the glass perimeter
- 11 The fins allow easy attachment of various GEALAN auxiliary profiles for customized installation situations

